



**SPECIFICATIONS**

- RATED SPEED: 3000RPM
- RATED CONTINUOUS TORQUE: 21 oz-in
- RATED POWER OUTPUT: 47 WATTS
- RATED TERMINAL VOLTAGE: 15.2 VOLTS
- RATED TERMINAL CURRENT: 7.26 AMPS
- MOMENT OF INERTIA: 0.0064 oz-in-sec<sup>2</sup>
- WEIGHT: 1.3 lbs

DRAWN		1/12/2007	
Sal			
MFG			
APPROVED			

**UNLESS OTHERWISE SPECIFIED**  
 1. DIMENSIONS ARE IN INCHES  
 2. TOLERANCES  
 ANGLES ±1°-30'  
 3. PLACEMENT ±.005  
 4. SURFACE ROUGHNESS ON MACHINED SURFACES  
 5. REMOVE ALL BURRS, BREAK SHARP EDGES TO .015 IN. MAX.  
 6. DIM. LIMITS ARE HLD. AFTER PLATING  
 7. MACHINED DIAS. ON A COMMON CENTER  
 8. LINE CONCENTRIC WITHIN .005 T.I.R.  
 9. UNMACHINED DIAS. CONCENTRIC WITHIN .031 T.I.R.  
 10. SQUARENESS AND PARALLELISM OF MACHINED SURFACES .002 PER INCH TO A MAX. OF .012 FOR A SINGLE SURFACE.

TITLE			
9AFB001			
PART NO		JOB NO	
9AFB001			
SCALE		REV	
SHEET 1 OF 1			